166	C C C C C C C C C C C C C C C C C C C	()	
- 54 - 24		<u>C</u>	<u>Closed Configuration</u>
<u> </u>			<u> Open Configuration</u>
	Load type Program load (PL)	Shear 420 kN	Tension Compression 500 kN 2000kN
	Breaking load (BL) Safe Working Load (SWL)	210 kN	500 kN 2000kN 250 kN 1000kN
Date: 14-07-2021	Revision no.: 001		Scale: 1:2.5
Color/finish: Hot Dip Galvanised	Weight: 4.5 kg		Drawn: K. van Puffelen
Material: Blank Steel	Comment: units in mm		Checked: S. Saeys
Manual Twistlock - Right Locking		A4	Drawingno.:
container parts			BD-A2-R
© Van Doorn Container Parts BV. All parts contained in this document is protected by the intellectual works of van Doorn container parts BV. Any form of copying, manufacturing or distribution towards third parties is strictly forbidden without the written permission of Van Doorn Container Parts BV. All care has been taken to prevent incorrectness, however Van Doorn Container Parts BV cannot be held responsible for incompleteness resulting from information containeed by this document. All rights are reserved by Van Doorn Container Parts BV.			

www.containerparts.nl / vandoorn@containerparts.nl / +31 (0)10-4296030

Γ