



















Why we select the best suppliers

Our suppliers have been market leaders for over decades in the production of new build container flooring.

They are good for over 50% of all production of new build container floors annually worldwide.

Due to our long term coorporation we are able to acquire the best Apitong sheets.

We have local experts to monitor the flow with our fixed factories so we can control the output and improve quality if necessarily.

Due to our very long business relationship we are very confident that all our factories will match our demand and needs.

The quality achieved fits in perfectly with our Viksin branded goods strategy.

High quality at affordable pricing.

Last but not least we choose always for A-grade repair plywood



Factory

- Viksin selects a quality factory
- Quality and packing will be monitored

Viksin

- Viksin will give feedback they receive from us back to the factory and will try to improve according to our guidelines
- They will supervise the contact with the factory

VD

- We will perform IICL short span test and the Maersk test
- We will guide CIMC to improove quality and packaging

Customer

- The customer will give quality feedback
- The customer will give packaging feedback

Why the VIKSIN label

VIKSIN is our full neutral brand that stands for high quality standards at affordable pricing

The VIKSIN stamp on the plywood gives you guarantee that the plywood after meeting all individual supplier quality standards will again be tested inhouse with our **9pcs** enhanced IICL short span test

On top of this test we will perform the new indicated MAERSK plywood quick test, which is a test that can be done in each depot without possesing proper testing equipment but will give a fairly good impression on the quality of the wood if done according to the MAERSK plywood quicktest guidelines


Viksin also supports traceabilty on all plywood sheets A unique batch code will be given to each plywood plate from the same container.

If any problems occur we can quickly act and find back all test results of the indicated batch



TYPE	DESCRIPTION
1010050108A	Apitong 1160x2400x28mm A-grade
1010050110A	Apitong 1160x2400x28mm A-grade black line
1010050106	Apitong 1220x2440x28mm A-grade
1010050109	Apitong 1220x2440x28mm A-grade black line
1010050103	Apitong 635x2400x28mm A-grade


How do we grade the plywood ?



What we guarantee with Our Viksin A-grade repair plywood:

- 1. The average breaking load of the 9 testsamples must be above 6780N
- 2. At least 6 pcs must be above 6780N
- 3. Maersk Quick plywood test must succeed

Unique traceability system including TG02 guidelines



Why 4 markings:

- 1. IICL surveyors will have full control and can rest assure the repair plywood is according to specs and testings
- 2. For the repair business not only full boards are used but also pieces, that is why VIKSIN opted for at least 4 markings of our unique batch number.
- 3. 1 board can be used for multiple repairs and can still be traced after a longer period
- 4. According to the new 2020 Container Owners association (COA) guidelines for depots TG02
- 5. The number is a unique batch number that VIKSIN provides together with the manufacturor on each batch so we can at any time have full control
- 6. VIKSIN on the stamp means the plywood has passed additional enhanced IICL short span test and has met T7 gradation and passed the Maersk Plywood test sold as A-grade Repair plywood

1. VD POXXXXXXXX VIKSIN DD-MM-YYYY CN 2400x1160x28 2. VD POXXXXXXXX VIKSIN

Enhanced and improved packaging



Improvement:

Smaller bundles of 30 plates

Strong flexible strappings

Corner protectors for strappings

Improvement on base

More and stronger carton for protection



Provided documents with each plywood delivery



Quality Control

Container Flooring - Short Span Bending Test

Report Date	24-8-2018	Purchase Order	11700455
Test Date	24-8-2018	Item	1010050108
		Description	Apitong 1160x2400x28mm Grade A

			Sample ID			
Characteristics	Requirement	Unit	XXX-1	XXX-2	XXX-3	
Ply Count	Minimum 19	[n]	19	21	20	
Width	50.8mm / 2"	[mm]	55,0	52,0	53,0	
Length	305 mm / 12"	[mm]	305,0	303,0	305,0	
Thickness	Minimum 28 mm +/- 1 mm	(mm)	27,00	28,00	27,00	
mass		(5)	344,7	353,7	353,7	
		[lbs]	0,76	0,78	0,71	
Calculate	i mass per sheet 28 mm x 1160 mm x 2400 mm	[9]	59.320,7	62.504,2	63.179,2	
		[lbs]	130,8	137,8	139,	
Span	254 mm / 10"	[mm]	254	254	254	
Breaking Load	Minimum 6000 N	[N]	9.434	10.818	11.058	
		[lbs]	2.121	2.432	2.486	
Result	Pass / Fail		Pass	Pass	Pass	

		53	8178	20.020	******
		[lbs]	2.12	2.432	2.486
Result	Pass / Fail		Pass	Pass	Pass
Images	XXX-1		XXX-2	XXX-3	
Test Setup					
-			The Act	THE PERSON	1
Test Failure					
					4
-	1 1 1 1 1 1		I K To	THE RES	1

Testing Equipment Jinan Zhongzheng Testing Machine Manufacturing Co. Ltd
MWD-108 - Manual Panel Testing Machine

IEA - Intermodal Equipment Alliance

CIMC CONTAINER CO., LTD

Production Date	8th Jul 2018		Inspection Date	10th Jul 2018		Report Number	20180710-01
Testing Item	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5	Specimen 6	Test Result
Thickness 28mm +/- 0.5mm	28.13	28.2	28.4	28.17	28.3	28.2	PASS
Width 51mm +/- 1mm	51.4	51.8	50.8	52	51.7	52	PASS
Length 305mm +/- 1mm	305	305.7	306	306	305.5	305	PASS
Density ≥0.744 g/cm3	0.763	0.763	0.763	0.763	0.763	0.763	PASS
IICL Short Span llax Load 1525lbf / 6900N	6980	6967	6954	7021	6984	6950	PASS
Modulus of Elasticity // ≥ 9000 Mpa	9142	9055	9138	9127	9161	9154	PASS
Modulus of Elasticity ⊥ ≥ 3200 Mpa	3246	3220	3244	3227	3216	3275	PASS
Modulus of Rupture // ≥ 77 Mpa	80	84	78	85	87	91	PASS
Modulus of Rupture ⊥ ≥ 32 Mpa	34	36	36	33	38	41	PASS
Moisture Content ≤12%	11	10	10	10	10	10	PASS

CIMC CONTAINER

Quality Control rapport

Rapport of product testing

Certificate of treatment

CIMC CONTAINER CO., LTD.

61, Yuejin Road, Tianjin Port Container Logistics Centre, Tang Gu, Tianjin 300461 P. R. C.

CERTIFICATE OF TREATMENT & TREATMENT DATA SHEET

THE BUYER : VAN DOORN CONTAINER PARTS B.V.
COMMODITY : CONTAINER FLOORING, GRADE A

WOOD SPECIES : KERUING & HARDWOOD

CONTRACT NO : EXF18066 PO11800988 QUANTITY : 266 PCS
PRODUCTION DATE : Jul 8-2018 ISSUED DATE : Jul 10-201

HE SPECIFICATION AND QUANTITY OF PROJ

SPECIFICATION(mm)	QUANTITY(PCS)	VOLUME (CBM)	
28×1160×2400	266	20.735	

TO WHOM IT MAY CONCER

THIS IS TO CERTIFY THAT ABOVE COMMODITY HAS BEEN TREATED WITH TAILLIEUM-400 BY CLUELINE METHOD TO A MINIMUM OF 0.5 $k_0^{\rm min}$ in accordance to the specification

TREATMENT RECORD AS RELOW

A. Mixing volume by wet glue	400	kg
Mixing volume by flour	24	kg
Mixing volume by Tailileum-400	1.70	kg
B. Glue spreaded quantity	0.35	kg/m ²
Number of glue spreaded core	10	plies
D. Thickness of plywood	28	mm
F. Retention charge of Tailileum-400 =0.35×1:	tel contractor of the party of the tree	

Issued b

CIMC CONTAINER CO., LTD.

天津中集

DCMANAGER



LASHING Material for Vessels / Containers & Roadtransport

Container Vessel

Fixed equipment

- flush
- raised
- varia

Loose equipment

- twistlock
- stackers
- turnbuckles
- lashing rods
- heigth adapters

Varia

- flatrack for lashing
- lashing bins
- tools

RO-RO Vessel

Fixed equipment

- flush
- raised
- D-rings

Loose equipment

- car lashings
- trailer lashing
- cargo lashing
- chocks
- trailerhorses

<u>Varia</u>

- chain lashing
- turnbuckles
- Loose items

General Cargo

Lashing

- steel plates
- dunnage
- D-rings
- turnbuckles
- lashing wire
- shackles
- lashing chain
- webbings

lifting equipment

- wires & grommers
- PES
- shackles
- complete lifting gear
- loose lifting gear
- spreaders

Dry-box parts

Plywood

Roof panels

Side Panels

Crossmembers

Cornerposts

Corner castings

Hinges

<u>Doorgaskets</u>

Latches

Doorrubber

Ventilation Covers

Stickers

Angle profiles

CSC plates

Screws and bolts

Silicones

<u>Paint</u>

Fork lift pockets

accessoires

Other parts

Tank parts

Containerparts ISO and specials

- Gauges
- Flanges
- Walkways
- Gaskets
- Handrailsets
- Isolation
- Fittings
- Documentholders

Reefer parts / Flatrack

- drains
- Body/floor/unit parts

Workshop

- Bending
- Cutting

