TYPE APPROVAL CERTIFICATE

Certificate no.:
TAS000025S
Revision No:
1

This is to certify:

that the Cargo Securing Devices

with type designation(s)
Dovetail plate double 55° AE-B2/203, Dovetail plate double 55° AE-B2/216, Dovetail plate double 55° AE-B2/258

issued to
General Lashing System (China) Co., Ltd.
Ningbo, **China**

is found to comply with
DNV class programme DNV-CP-0068 – General – Certification of container securing devices

Application:

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Type	SWL, tension (kN)	SWL, shear (kN)
Dovetail plate double 55° AE-B2/203	250	210
Dovetail plate double 55° AE-B2/216	250	210
Dovetail plate double 55° AE-B2/258	250	210

Issued at **Hamburg** on **2024-08-08**

This Certificate is valid until **2029-08-07**.
DNV local unit: **Ningbo FIS**

Approval Engineer: **Aadil Wafdi**

for **DNV**

Digitally Signed By: Wobig, Mark-Oliver
Location: DNV Hamburg, Germany
Signing Date: 06.08.2024

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Product description

Dovetail plate

Application/Limitation

Load	Tension [kN]	Shear [kN]
Test Load	375	315
Breaking Load	500	420

Tests to be carried out:

- Production testing: At least 2% of the items delivered are to be selected and subjected to the test load.
- Material tests are to be included energy testing at -20°C, with the impact energy requirements acc. to DNV-CP-0068. The material shall be according to the approved drawings. Material certificates shall be 3.1 acc. to ISO 10474:2013.

Type Approval documentation

Drawing No.	Rev.	Title
AE-B2		Dovetail plate double 55°

Drawing Approval: GL Ref.-No.: 09-034072 Date: 2009-03-02
Test report No.: CP-0068 dated 2024-07-01

Tests carried out

The prototype test was carried out in Ningbo, P.R. China, dated 2024-07-01 in accordance with the DNV-CP-0068.

Marking of product

Each item shall be marked by manufacturer for traceability.

Periodical Assessment

For retention of the Type Approval, a DNV surveyor shall perform a survey after 2 and 3.5 years, to verify that the Type Approval is complied with.